

ADVANCED



Spirobank II™ Advanced

Spirometer with Oximetry Option

Portable minilab for **pulmonologists and respiratory therapists**

Real-time tests with **wireless Bluetooth™** and **USB**

Rechargeable, **long-life battery**

Traffic lights for immediate test interpretation

SpO2 and pulse rate (optional) directly on the display (including **plethysmographic curve**)



Always included: Winspiro PRO™ PC software with free update



MIR SpiroPRO™ New Spirometry software for **Windows and MacOs**



Available with both **DISPOSABLE** or **REUSABLE** turbine flowmeter



Spirometry test: FVC, VC, IVC, MVV, PRE/POST Bronchodilator comparison with a wide range of selectable parameters



Optional function available: Oximeter with adult or paediatric finger probe

Minispir™

Computer-based Spirometer

Real time Flow/Volume and Volume/Time curves on your PC for a comprehensive Spirometry

Includes a wide range of selectable parameters

Spirometry test interpretation

Embedded Temperature sensor for BT/PS conversion



Always included: Winspiro PRO™ PC software with free update



MIR SpiroPRO™ New Spirometry software for **Windows and MacOs**



Available with both **DISPOSABLE** or **REUSABLE** turbine flowmeter



Spirometry test: FVC, VC, IVC, MVV, PRE/POST Bronchodilator comparison with a wide range of selectable parameters



Technical specification

Width	49.7 mm
Length	142 mm
Thickness	26 mm
Weight	65 g

Turbine



Reusable turbine
(code 910002)



Disposable turbine
(code 910004)

Supply voltage	5 V d.c. USB connection
Frequency	--
Rated electrical power	0.25 W
Rated input current	50 mA max
Backup battery voltage	none
Connectivity	USB 2.0
Display	none
Keyboard	none
Mouthpieces	Ø 30 mm (1.18 inch)
Type of electrical protection	Class II device
Safety level for shock hazard	Type BF Apparatus
Conditions of use	Apparatus for continuous use
Storage conditions	Temperature: MIN -40 °C, MAX + 70 °C Humidity: MIN 10% RH; MAX 95%RH
Operating Conditions	Temperature: MIN + 10 °C, MAX + 40 °C Humidity: MIN 10% RH, MAX 95%RH
Applied norms	Electrical Safety Standard EN 60601-1 Electro Magnetic Compatibility EN 60601-1-2
PC software	winspiroPRO

Spirometry

Flow sensor	bi-directional digital turbine
Volume range	10 L
Flow range	±16L/s
Volume accuracy	±3% or 50 mL
Flow accuracy	±5% or 200 mL/s
Dynamic resistance	<0.5 cm H2O/L/s
Temperature sensor	semiconductor (0-45°C)
Test available	FVC, VC, IVC, MVV, PRE-POST FVC, FEV1, FEV1/FVC%, FEV3, FEV3/FVC%, FEV6, FEV1/FEV6%, PEF, FEF25%, FEF50%, FEF75%, FEF25-75%, FET, Vext, Lung Age, EVOL, FIVC, FIV1, PIF, FIV1/FIVC%, PIF, IRV, VC, IVC, IC, ERV, FEV1/VC%, VT, VE, Rf, ti, te, ti/t-tot, VT/ti, MVV
Measured parameters	
Memory capacity	database PC software

Oximetry (on request)

Measurement method	Red and infrared absorption
SpO2 range	0-99%
SpO2 accuracy	± 2% between 70-99% SpO2
Average number of heart beats for the %SpO2 calculation	8 beats
Pulse Rate range	18-300 BPM
Pulse Rate accuracy	± 2BPM or 2% whichever is greater
Average interval for the calculation of cardiac pulse	8 seconds
Signal quality indication	0 - 8 segments on display
Test available	spot
Measured parameters	SpO2% min, max, average BPM min, max, average Test duration % Bradycardia Duration (<40 BPM) % Tachycardia Duration (>120 BPM) % of Time with SpO2 ≤ 90% (T90%, T89%)
Memory capacity	database PC software

Certificates & Registrations

CE 0476	MED 9826
FDA 510 (k)	K 122384
Health Canada	71191 (class II)
CND code	Z12150102
GMDN code	13680
Ministry of Health	678828/R