



Thermo

WARMING CABINET

Warming cabinet intended for warming of IV fluids, irrigation solutions, linens and blankets.

FEATURES

- 24h set temperature maintenance
- Uniform warming of fluids and linen
- Fast warming time (20-60 min depending on the set and ambient temperatures)
- Different sizes available (120, 180, 360 lt)
- Dual compartment models
- Stainless steel structure

APPLICATION

Can be installed in pre-operating rooms, nurse's stations, examination and medical treatment rooms, etc.

CONTROL SYSTEM

- LED display
- Indication of current and set temperatures
- Indication of time since heating start
- 2 heating modes: «Solutions» and «Linen»
- Door open indicator
- Audible and visual alarms
- RFID-card for control panel locking
- Self-diagnostic system at the power-up



- Stainless steel shelves
- Extendable and removable shelves for convenient use and easy disinfection of internal surfaces
- Door lock
- Left- or right-hinged door



MODULAR SYSTEM

Combination of models with control panel for each compartment:

- S+S
- M+M
- M+S
- L+S



Thermo S



Thermo M



Thermo L

Volume	120 litres	180 litres	360 litres
Dimensions (Width x Depth x Height)	670x640x580 mm	670x640x840 mm	670x640x1450 mm
Number of shelves	2	3	5
Weight	50 kg	60 kg	75 kg
Maximum power consumption	250 W	450 W	700 W
Supply voltage / frequency	110-230 VAC, 50/60 Hz		
Temperature settings	34°C - 60°C		
Temperature increment	0.5°C		
Average warming time (at an initial t 20°C)			
- to 34°C	20 min		
- to 42°C	35 min		
- to 60°C	60 min		
Continuous operation	24h		
Electric shock protection class	B/I		
Protection class	IP23		



OPTIONS

- Stationary
- Mobile

* Castor wheels with different diameters available